



L: 167 mm; W: 115 mm; H: 152 mm

Features & Benefits:

- Multi-Functional for a Wide Range of Applications
- Easy to Use with Omni-Directional Reading and Large Read Window

E-Ticket/Phone Reader

JADAK's PR-1 is a 1D and 2D barcode reader designed to read directly from cell phone screens, mobile or personal device screens, and paper. With a small footprint, the PR-1 can be used on a desktop, mounted on a wall, or integrated flush in a counter.

For ease of use, the PR-1 provides omni-directional reading, reducing alignment issues associated with presenting and reading barcodes. The large read window accommodates larger barcodes and makes presentation easier. PR-1 also provides a red-green indicator light for user feedback based on application and security requirements.

PR-1's metal housing makes this reader rugged for high volume use.

Applications:

- Airplane Boarding
- Venue Attendance
- Security Checkpoints
- Ticket-Based Entrances



JADAK

A Novanta Company

Performance	
Light Source	Interior Window Illumination
Presentation	360°
Ambient	Total Darkness to 100,000 Lux (Sunlight)
Software	Imageview Configuration
Mechanical/Electrical	
Dimensions (L x W x H)	167 mm x 115 mm x 152 mm
Scanning Current	330mA max
Power Supply	12v +/- 5%
Interface Cable	RJ45 to USB type A, 15-meter length
Communication	
Communications	USB COMM Port Emulation
Environmental	
Operating Temperature	0° to 50°C (32° F to 122° F)
Humidity	95% relative humidity, noncondensing, at 50°C
Agency	FCC Class B, CE, IEC Class 1 (Laser Aimer)
Agency	RoHS and WEEE Compliance
Supported Symbologies	
Linear	Code 39, Code 128, Codabar, UPC, EAN, Interleaved 2 of 5, Reduced Space Symbology, Code 93, Codablock
2D	PDF417, MicroPDF 417, DataMatrix, QR Code, Aztec Code, Maxicode, Aztec Mesa, Code 49, UCC Composite

