

Allegro SONY IMX172 12.4MP



US3
VISION

SPECIFICATIONS

Image Sensor Model	Sony Starvis IMX172
Sensor Format	1/2.3 inch
Max Resolution	4000 x 3000, 12MP
Max Frame Rate	32 fps (mono)
Burst Frame Rate	35 fps into internal buffer
Pixel Size	1.55 um x 1.55 um
Shutter	Rolling
Vision Standard	USB3 Vision™ Specification v1.0
Analog-to-Digital Converter	12-bit ADC
Sensor Video Data	12-bit digital data
Image Data Formats	YUV, YCbCr422/400, RGB8/565, processed Bayer8/10/12, Mono8/10/12, including packed
FPGA	Altera Cyclone V
On-Board Memory	256 MB
Dynamic Range	72 dB and other High Dynamic Range modes available
Partial Image Modes	2 x 2 Binning is supported. Programmable region of interest capability.
Gain Control	Analog Gain & Digital Gain (programmable)
Shutter Speed	Manual / One-push modes, programmable from 0.03 ms to 1 sec, longer exposure (integration) times can be supported if needed
Synchronization	Via external trigger and software trigger
Trigger Latency / Jitter	Latency TBD / Jitter +/- 0.5 microsecond
Interface Port	USB3
General Purpose I/O Port	12 Pin 7 mm Push-Pull Connector Programmable Opto-Isolated Trigger Input 2 Programmable Opto-Isolated Strobe Outputs
Power / Voltage	USB3 Host Port, 5 V +/- 10% at 0.9 A max
Dimensions (W x H x L)	52 x 46 x 33 mm (camera body)
Mass	126 g (without optics)
Lens Mount	C-Mount or CS-Mount (optional)
Adjustable Back Focal Length	Optional
Emissions Compliance	CE, FCC, RoHS
Operating Temperature	-0° to 50° C
Storage Temperature	-30° to 70° C
Vibration Resistance	10 G (14 Hz to 200 Hz)
LED Indicator	Status and power monitoring Dual color
Enclosure	Pre-drilled mounting holes Tripod mount available Heavy duty aluminum Sealed Sensor Cavity
Warranty	4 years – Industry leading

© Novanta 2018 Rev. 09062018

USA Office

phone:+1 315.701.0678
email: info@jadaktech.com
web: jadaktech.com

European Office

phone:+31 (0)76.522.5588

Asia Pacific Office

phone:+86.512.6283.7080



JADAK
A Novanta Company

 **Novanta**