

Allegro SONY IMX255 8.9MP



SPECIFICATIONS

Image Sensor Model	Sony Pregius IMX255
Sensor Format	1 inch
Max Resolution	4096 x 2160, 8.9 MP
Max Frame Rate	14 fps (mono)
Burst Frame Rate	46.5 fps into internal buffer (mono)
Pixel Size	3.45 x 3.45 μm
Shutter	Global
Vision Standard	GigE Vision™ Specification v1.1
Analog-to-Digital Converter	12-bit ADC
Sensor Video Data	10-bit, 12-bit digital data
Image Data Formats	YUV, YCbCr422/400, RGB8/565, processed Bayer8/10/12, Mono8/10/12, including packed
FPGA	Altera Cyclone V
On-Board Memory	256 MB
Dynamic Range	72 dB and other High Dynamic Range Modes Available
Partial Image Modes	2 x 2 Binning is supported. Programmable region of interest capability.
Gain Control	Analog Gain & Digital Gain (programmable)
Shutter Speed	Manual / One-push auto modes. Programmable from 0.03 ms to 1 sec. Longer exposure (integration) times can be supported if needed.
Synchronization	Via external trigger
Trigger Latency / Jitter	Latency TBD, Jitter +/- 0.5 microsecond
Interface Port	Gigabit Ethernet RJ45
General Purpose I/O Port	12 Pin 7 mm Push-pull connector Programmable opto-isolated trigger input 2 Programmable opto-isolated strobe outputs
Power / Voltage	Via 12 pin Push-pull connector 6 V at 2 A or USB3 connector 5 V +/- 10% at 0.9 A max
Dimensions (W x H x L)	52 x 46 x 39 mm (camera body)
Mass	140 g (without optics)
Lens Mount	C-Mount or CS-Mount
Adjustable Back Focal Length	Optional
Emissions Compliance	CE, FCC, RoHS
Operating Temperature	-0° to 50° C
Storage Temperature	-30° to 70° C
Vibration Resistance	10 G (14 Hz to 200 Hz)
LED Indicator	Status and power monitoring Dual color
Enclosure	Pre-drilled mounting holes Tripod mount available Heavy duty aluminum Sealed Sensor Cavity
Warranty	4 years – Industry leading

© Novanta 2018 Rev. 09062018

USA Office

phone:+1 315.701.0678
email: info@jadaktech.com
web: jadaktech.com

European Office

phone:+31 (0)76.522.5588

Asia Pacific Office

phone:+86.512.6283.7080



JADAK
A Novanta Company

